



# 2632EX EXPLOSION PROOF SCISSOR LIFT

## SPECIFICATIONS

|                                  |                      |             |
|----------------------------------|----------------------|-------------|
| Working Height                   | 32 ft                | 9.8 m       |
| Raised Platform Height           | 26 ft                | 7.9 m       |
| Lowered Platform Height          | 45 in                | 1.1 m       |
| Platform Size (inside)           | 28 x 84 in           | 0.7 x 2.1 m |
| Platform Capacity                | 500 lbs              | 227 kg      |
| Overall Width                    | 32 in                | 0.8 m       |
| Overall Length                   | 108 in               | 2.75 m      |
| Stowed Height                    | 84.7 in              | 2.2 m       |
| Deck Extension                   | 3 ft                 | 0.92 m      |
| Ground Clearance (Stowed)        | 3.5 in               | 8.9 cm      |
| Ground Clearance (Raised)        | 0.75 in              | 1.9 cm      |
| Wheelbase                        | 69 in                | 1.8 m       |
| Inside Turning Radius            | 50 in                | 1.3 m       |
| Outside Turning Radius           | 108 in               | 2.7 m       |
| Drive Speed (Stowed)             | 1 mph                | 1.6 km/h    |
| Drive Speed (Raised)             | 0.5 mph              | 0.8 km/h    |
| Batteries                        | 4 x 6V 250 Amp-hr    |             |
| Charger                          | 20 Amp Automatic SCR |             |
| Specifications Subject to Change |                      |             |



## SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

## STANDARD EQUIPMENT

- 26 ft Platform Height
- 32 ft Working Height
- 28 x 84 in Platform Size
- 3.5 in Ground Clearance
- 500 lb Platform Capacity
- 3 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

## OPTIONS\*

- Padded Aircraft Rails
- Vertical Access Aid
- Enhanced Padded Aircraft Rails
- 1/2" Airline to Platform
- Fall Arrest System

\*May Change Capacity

