



# 2668EX EXPLOSION PROOF SCISSOR LIFT

| SPECIFICATIONS                   |            |             |
|----------------------------------|------------|-------------|
| Working Height                   | 32 ft      | 9.8 m       |
| Raised Platform Height           | 26 ft      | 7.9 m       |
| Lowered Platform Height          | 50 in      | 1.3 m       |
| Platform Size (inside)           | 57 x 84 in | 1.4 x 2.1 m |
| Platform Capacity                | 1200 lbs   | 544 kg      |
| Overall Width                    | 68 in      | 1.7 m       |
| Overall Length                   | 118.5 in   | 3.01 m      |
| Stowed Height                    | 95.5 in    | 2.4 m       |
| Deck Extension                   | 5 ft       | 1.5 m       |
| Ground Clearance (Stowed)        | 7.5 in     | 19.1 cm     |
| Ground Clearance (Raised)        | 0.7 in     | 1.8 cm      |
| Wheelbase                        | 76 in      | 1.93 m      |
| Inside Turning Radius            | 76 in      | 1.93 m      |
| Outside Turning Radius           | 164 in     | 4.2 m       |
| Drive Speed (Stowed)             | 1 mph      | 1.6 km/h    |
| Drive Speed (Raised)             | 0.5 mph    | 0.8 km/h    |
| Specifications Subject to Change |            |             |



## SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

## STANDARD EQUIPMENT

- 26 ft Platform Height
- 32 ft Working Height
- 57 x 84 in Platform Size
- 7.5 in Ground Clearance
- 1200 lb Platform Capacity
- 5 ft Extendable Deck
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

## OPTIONS\*

- Padded Aircraft Rails
- Vertical Access Aid
- Enhanced Padded Aircraft Rails
- 1/2" Airline to Platform
- 5 ft Powered Extension Deck
- Fall Arrest System

\*May Change Capacity

