



3268EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS		
Working Height	38 ft	11.6 m
Raised Platform Height	32 ft	9.8 m
Lowered Platform Height	54 in	1.37 m
Platform Size (inside)	56 x 96 in	1.4 x 2.44 m
Capacity (Overall)	1,000 lbs	454 kg
Overall Width	69.5 in	1.76 m
Overall Length	107 in	2.72 m
Stowed Height (Rails Up)	99 in	2.51 m
Stowed Height (Rails Down)	69 in	1.75 m
Deck Extension	5 ft	1.52 m
Ground Clearance	8 in	0.20 m
Maximum Drive Height	Full Height	
Wheelbase	80.5 in	2.04 m
Inside Turning Radius	60 in	1.52 m
Outside Turning Radius	156 in	3.96 m
Drive Speed (Stowed)	3.8 mph	6.1 km/h
Drive Speed (Raised)	0.5 mph	0.8 km/h
Specifications Subject to Change		



SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

STANDARD EQUIPMENT

- 32 ft Platform Height
- 38 ft Working Height
- 56 x 96 in Platform Size
- 8 in Ground Clearance
- 1,000 lb Capacity
- 5 ft Extendable Deck
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

OPTIONS*

- Padded Aircraft Rails
- Vertical Access Aid
- Enhanced Padded Aircraft Rails
- 1/2" Airline to Platform
- Fall Arrest System

*May Change Capacity

