



5392EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	59 ft	17.98 m
Raised Platform Height	53 ft	16.15 m
Lowered Platform Height	83.5 in	2.12 m
Platform Size (inside)	71.7 x 171.7 in	1.82 x 4.4 m
Platform Capacity	1,500 lbs	680 kg
Overall Width	90.6 in	2.3 m
Overall Length	177 in	4.5 m
Stowed Height (Rails Up)	126 in	3.2 m
Stowed Height (Rails Down)	95.7 in	2.43 m
Deck Extension	5 ft	1.5 m
Ground Clearance	10 in	26 cm
Wheelbase	119 in	3.0 m
Inside Turning Radius	131 in	3.33 m
Drive Speed (Stowed)	3.5 mph	5.6 km/h
Drive Speed (Raised)	0.6 mph	1 km/h
Batteries	8 x 6V 420 Amp-hr	
Charger	Automatic SCR	
Specifications Subject to Change		



SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

STANDARD EQUIPMENT

- 53 ft Platform Height
- 59 ft Working Height
- 72 x 172 in Platform Size
- 10 in Ground Clearance
- 1,500 lb Platform Capacity
- 5 ft Extendable Deck
- 500 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

OPTIONS*

- Padded Aircraft Rails
- Vertical Access Aid
- Enhanced Padded Aircraft Rails
- 1/2" Airline to Platform
- 5 ft Powered Extendable Deck
- Dual 5 ft Roll-out or Powered Extendable Decks
- Remote Mount 600 Amp Charger & Battery
- Platform Battery Condition Indicator
- Lithium Ion Battery
- FMR System Fault Monitoring and Recording
- Fall Arrest System

*May Change Capacity



BaileyCranes.com | sales@baileycranes.com | 262-710-4028